

(ALIDでの入力パラメータ)

品番	製品基準強度	設計強度	設計強度	単位重量	断面積	引張剛性	変形係数
	T _{max} (kN/m)	T _A (kN/m)	T _{AE} (kN/m)	γ (kN/m ³)	A (m ²)	EA (kN/m)	E (kN/m ²)
50L	50	31	39	0.0043	0.000418	500	1,196,172
100L	100	63	79	0.0043	0.000463	1,000	2,159,827
150L	150	95	119	0.0052	0.000549	1,500	2,732,240
200L	200	126	158	0.0059	0.000570	2,000	3,508,772
250L	250	158	198	0.0072	0.000684	2,500	3,654,971
300L	300	190	238	0.0081	0.000784	3,000	3,826,531
400L	400	253	317	0.0110	0.001080	4,000	3,703,704
500L	500	332	416	0.0134	0.001255	5,000	3,984,064
600L	600	399	449	0.0157	0.001751	6,000	3,426,613
700L	700	466	582	0.0181	0.001927	7,000	3,632,590
800L	800	532	665	0.0208	0.002184	8,000	3,663,004
900L	900	599	748	0.0235	0.002548	9,000	3,532,182
1000L	1000	665	832	0.0260	0.002775	10,000	3,603,604